SAFETY DATA SHEET
(in accordance with Regulation (EU) 2020/878)

SPRAY LIMPIADISCOS

Version 1 Date of compilation: 28/03/2022
Version 3 (replaces version 2) Revision date: 18/05/2024
Print date: 18/05/2024

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name:	SPRAY LIMPIADISCOS
Product Code:	N017
UFI:	5S00-V0W2-M009-04YJ

1.2 Relevant identified uses of the substance or mixture and uses advised against.
BICYCLE DISC CLEANER.

Uses advised against:
Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company:	**JOSE LASTRA CISNEROS**
Address:	C/ DEL POZO, 8
City:	49002 - ZAMORA
Province:	ZAMORA
Telephone:	+34 980 532985
E-mail:	navali@navali.es

1.4 Emergency telephone number: +34 980 532985 (Only available during office hours; Monday-Friday; 08:00-18:00)
general EU emergency numbers (112 / 116117)
ESPAÑA :Servicio de Información Toxicológica (Instituto Nacional de Toxicología y Ciencias Forenses) Teléfono: +34 91 5620420. Información en español (24h/365 días). Únicamente con la finalidad de proporcionar respuesta sanitaria en caso de urgencia.
FRANCE : ORFILA (INRS) : + 33 (0)1 45 42 59 59. 24 heures sur 24 et 7 jours sur 7.
CAV Policlinico "Umberto I"Roma V.le del Policlinico, 155 161T.:06-49978000 .Az. Osp. "Careggi" U.O. Tossicologia Medica Firenze Largo Brambilla, 3 50134 055-7947819.Osp. Niguarda Ca' Granda Milano Piazza Ospedale Maggiore,3 20162 02-66101029. Az. Osp. "A. Cardarelli" Napoli Via A. Cardarelli, 9 80131 081-5453333
PORTUGAL: Em caso de intoxicação contactar o Centro de Informação Antivenenos (CIAV) (+351) 800 250 250. Atendimento médico 24 horas por dia, 7 dias por semana.

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.
In accordance with Regulation (EC) No 1272/2008:
Aerosol 1 : Pressurised container: May burst if heated.
Eye Irrit. 2 : Causes serious eye irritation.
Flam. Gas 1A : Extremely flammable gas.
STOT SE 3 : May cause drowsiness or dizziness.

2.2 Label elements.
Labelling in accordance with Regulation (EC) No 1272/2008:
Pictograms:



Signal Word:
Danger

Hazard statements:

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary statements:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.
P377	Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381	In case of leakage, eliminate all ignition sources.
P403	Store in a well-ventilated place.
P501	Dispose of contents/container in accordance with local/national/international regulation.

Contains:
propan-2-ol, isopropyl alcohol, isopropanol

2.3 Other hazards.
The mixture does not contain substances classified as PBT.
The mixture does not contain substances classified as vPvB.
The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.
Not applicable.

3.2 Mixtures.
Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	Specifics concentration limits and Acute toxicity estimate
Index No: 603-117-00-0 CAS No: 67-63-0 EC No: 200-661-7 Registration No: 01-2119457558-25-XXXX	[2] propan-2-ol, isopropyl alcohol, isopropanol	>= 50% < 75 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-
Index No: 603-019-00-8 CAS No: 115-10-6 EC No: 204-065-8 Registration No: 01-2119472128-37-XXXX	[1] [2] dimethyl ether	>= 25% < 50 %	Flam. Gas 1A, H220	-

(*) *The complete text of the H phrases is given in section 16 of this Safety Data Sheet.*
[1] Substance with a European Union exposure limit in the workplace (see section 8.1).
[2] Substance with a national workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.
In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.
Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Dont let the person to rub the affected eye.

Skin contact.
Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.
If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.
Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

4.3 Indication of any immediate medical attention and special treatment needed.
In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

SECTION 5: FIREFIGHTING MEASURES.

In case of fire, as a general hazard, heat can cause containers to explode.
The product is Extremely inflammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

5.1 Extinguishing media.
Suitable extinguishing media:
Extinguisher powder or CO2.

Unsuitable extinguishing media:
Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.
Special risks.
Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:
- Flammable vapors or gases.
- Explosions.

5.3 Advice for firefighters.
Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Follow the instructions given in the emergency or fire evacuation plan or plans if available. Move containers away from the area if there is no danger in doing so. Keep away from containers and continue cooling them from a safe place. Stop the leak if this can be done safely and do not put out fire until the leak has been closed off. If it is not possible to keep the fire under control, leave the area and let it burn.

Fire protection equipment.
According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.
Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. Isolate the area and ensure adequate ventilation. Stockpiling in basements, pits or any confined space or depressed area can be hazardous. Use a self-contained breathing apparatus when the atmosphere is not suitable to be breathed. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product not classified as hazardous for the environment, avoid spillage as much as possible.

6.3 Methods and material for containment and cleaning up.
Use soapsuds to detect small leaks. Stop the leak if this can be done safely. Ensure adequate ventilation to prevent the accumulation of gases or vapours.

En caso de que el gas condense:
Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant. Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.
For exposure control and individual protection measures, see section 8.
For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.
The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.
The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.
Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.
In the application area, smoking, eating, and drinking must be prohibited.
Follow legislation on occupational health and safety.
Pressurised gases must be handled by suitably trained and experienced individuals. Use equipment suitable for supply pressure and temperature. Protect containers against physical damage and keep valves clean and in perfect condition. Do not tamper with original packaging.

7.2 Conditions for safe storage, including any incompatibilities.
Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 º C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. It must not be stored under conditions conducive to corrosion of the container. Protect containers against physical damage and inspect them regularly to ensure they are in good condition.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).
Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m³
propan-2-ol, isopropyl alcohol, isopropanol	67-63-0	Deutschland [1] (n/a)	**Eight hours**	200	500
			Short term	200	500
		España [2]	**Eight hours**	200	500
			Short term	400	1000
		France [3]	**Eight hours**		
			Short term	400	980
		United Kingdom [4]	**Eight hours**	400	999
			Short term	500	1250
		Italia [5]	**Eight hours**	200	
			Short term	400	

		Portugal [6] (n/a)	**Eight hours**	200	
			Short term	400	
		Sverige [7] (n/a)	**Eight hours**	150	350
			Short term	250	600
		United States [8] (Cal/OSHA)	**Eight hours**	400	
			Short term	500	
		United States [9] (NIOSH)	**Eight hours**	400	
			Short term	500	
		United States [10] (OSHA)	**Eight hours**	400	980
			Short term		
dimethyl ether	115-10-6	Deutschland [1] (n/a)	**Eight hours**	1000	1900
			Short term	2000	3800
		España [2]	**Eight hours**	1000	1920
			Short term		
		European Union [11]	**Eight hours**	1000	1920
			Short term		
		France [3]	**Eight hours**	1000	1920
			Short term		
		United Kingdom [4]	**Eight hours**	400	766
			Short term	500	958
		Italia [5]	**Eight hours**	1000	1920
			Short term		
		Portugal [6] (n/a)	**Eight hours**	1000	1920
			Short term		
		Sverige [7] (n/a)	**Eight hours**	500	950
			Short term	800	1500

Biological exposure limit values for:

Name	CAS No.	Country	Biological indicator	BLV	Sampling time
propan-2-ol, isopropyl alcohol, isopropanol	67-63-0	España [2]	Acetona en orina	40 mg/l	Final de la semana laboral
		Portugal [6] (n/a)	Acetona na urina	40 mg/L	Fim do turno no fim da semana de trabalho

[1] Laut Grenzwerte in der Luft am Arbeitsplatz "Luftgrenzwerte" verabschiedet vom Bundesminister für Arbeit und Sozialordnung im Bundesarbeitsblatt.
[2] Según la lista de Valores Límite Ambientales de Exposición Profesional adoptados por el Instituto Nacional de Seguridad y Salud en el Trabajo (INSST) para el año 2023.
[3] Selon la liste de Valeurs limites d'exposition professionnelle aux agents chimiques en France adoptés par Institut national de la recherche scientifique.
[4] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adobted by Health and Safety Executive.
[5] Secondo il Decreto Legislativo del Governo n.277, 15/08/1991, il Decreto Legislativo n.66 ed il Decreto Ministeriale 26/02/2004.
[6] De acordo com a Norma Portuguesa 1796 adotou pelo Instituto português de qualidade.
[7] According Occupational Exposure Limit Values and Measures against Air Contaminants adopted by Swedish Work Environment Authority.
[8] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).
[9] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.
[10] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).
[11] According both Binding Occupational Esposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
propan-2-ol, isopropyl alcohol, isopropanol CAS No: 67-63-0	DNEL (Workers)	Inhalation, Chronic, Systemic effects	500 (mg/m³)

EC No: 200-661-7	DNEL (Consumers)	Inhalation, Chronic, Systemic effects	89 (mg/m³)
	DNEL (Workers)	Dermal, Chronic, Systemic effects	888 (mg/kg bw/day)
	DNEL (Consumers)	Dermal, Chronic, Systemic effects	319 (mg/kg bw/day)
	DNEL (Consumers)	Oral, Chronic, Systemic effects	26 (mg/kg bw/day)
dimethyl ether CAS No: 115-10-6 EC No: 204-065-8	DNEL (Workers)	Inhalation, Chronic, Systemic effects	1894 (mg/m³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
Concentration levels PNEC:

Name	Details	Value
propan-2-ol, isopropyl alcohol, isopropanol CAS No: 67-63-0 EC No: 200-661-7	aqua (freshwater)	140,9 (mg/L)
	aqua (marine water)	140,9 (mg/L)
	aqua (intermittent releases)	140,9 (mg/L)
	sediment (freshwater)	552 (mg/kg sediment dw)
	sediment (marine water)	552 (mg/kg sediment dw)
	Soil	28 (mg/kg soil dw)
	STP	2251 (mg/L)
	oral (Hazard for predators)	160 (mg/kg food)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

8.2 Exposure controls.

Measures of a technical nature:
Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	**100 %**
Uses:	**BICYCLE DISC CLEANER.**
Breathing protection:	
PPE:	Filter mask for protection against gases and particles.
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.
CEN standards:	EN 136, EN 140, EN 405
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.
Filter Type needed:	A2
Hand protection:	
PPE:	Work gloves.
Characteristics:	«CE» marking, category I.
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.

Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480	Material thickness (mm):	0,35

Eye protection:	
PPE:	Face shield.
Characteristics:	«CE» marking, category II. Face and eye protector against splashing liquid.
CEN standards:	EN 165, EN 166, EN 167, EN 168
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly.
Observations:	Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame.
Skin protection:	
PPE:	Anti-static protective clothing.
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.
PPE:	Anti-static safety footwear.
Characteristics:	«CE» marking, category II.
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346
Maintenance:	The footwear should be checked regularly
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.
Physical state: Aerosol
Colour: Colourless
Odour: Characteristic
Odour threshold: Not available
Melting point: Not available
Freezing point: Not available
Boiling point or initial boiling point and boiling range: Not applicable (Column 2 of Annex VII, REACH)
Flammability: Not available
Lower explosion limit: Not available
Upper explosion limit: Not available
Flash point: -41 ºC
Auto-ignition temperature: 240 ºC
Decomposition temperature: Not available
pH: Not applicable (Substance/mixture is a gas).
Kinematic viscosity: Not applicable
Solubility: Not applicable
Hydrosolubility: Not applicable
Liposolubility: Not applicable
Partition coefficient n-octanol/water (log value): Not applicable
Vapour pressure: 1.651,926 (Estimation based on the indication of the Regulation (CE) Nº1272/2008.)
Absolute density: Not applicable/Not available due to the nature/properties of the product
Relative density: 0.744
Relative vapour density: Not available
Particle characteristics: Not available

9.2 Other information
Other safety characteristics
Viscosity: Not available
Dropping point: Not applicable
Blink: Not applicable
% Solids: Not applicable

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.
The product does not present hazards by their reactivity.

10.2 Chemical stability.
Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.
Extremely flammable aerosol.
Pressurised container: May burst if heated.

10.4 Conditions to avoid.
Avoid any improper handling.

10.5 Incompatible materials.
Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.
No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. Splashes in the eyes can cause irritation.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

11.1 Information on hazard classes as defined in Regulation (EC) Nº 1272/2008.
Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
propan-2-ol, isopropyl alcohol, isopropanol CAS No: 67-63-0 EC No: 200-661-7	Oral	LD50 [1] Guideline OECD 401	Rat	5840 mg/kg bw [1]
	Dermal	DL50 [1] Guideline OECD 402	Rabbit	12800 mg/Kg [1]
	Inhalation	CL50 [1] OECD 403	Rat	72600 mg/m3 (4H) [1]
dimethyl ether CAS No: 115-10-6 EC No: 204-065-8	Oral			
	Dermal			
	Inhalation	CL50 LC50	Rat Rat	309 mg/L (4H) 164 mg/L (4h)

a) acute toxicity;
Not conclusive data for classification.

b) skin corrosion/irritation;
Not conclusive data for classification.

c) serious eye damage/irritation;
Product classified:

Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;
Not conclusive data for classification.

e) germ cell mutagenicity;
Not conclusive data for classification.

f) carcinogenicity;
Not conclusive data for classification.

g) reproductive toxicity;
Not conclusive data for classification.

h) STOT-single exposure;
Product classified:
Specific target organ toxicity following a single exposure, Category 3: May cause drowsiness or dizziness.

i) STOT-repeated exposure;
Not conclusive data for classification.

j) aspiration hazard;
Not conclusive data for classification.

11.2 Information on other hazards.
Endocrine disrupting properties
This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information
There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
propan-2-ol, isopropyl alcohol, isopropanol CAS No: 67-63-0 EC No: 200-661-7	Fish	CL50	P.promelas	9640 mg/L (96h) [1]
		[1] Guideline OECD 203		
	Aquatic invertebrates	LC50	Daphnia magna	>10000 mg/l (24 h) [1]
		EC50	D.magna	10.000 mg/L (48h)
		[1] Not GLP, no guideline followed, although it is similar to the most recent OECD 202 with some deviations, which did not affect results. It contains all the information necessary for the evaluation.		
	Aquatic plants	CE50	Algae	>1000 mg/L (72H) [1]
		EC50	Green algae	1.800 mg/L (7d)
		[1] OECD 201		
dimethyl ether CAS No: 115-10-6 EC No: 204-065-8	Fish	CL50	PECES	4100 mg/L (96H)
		LC50	S,gairdneri	3082 mg/L (96)
	Aquatic invertebrates	CE50	Daphnia magna	4400 mg/L (48h)
		CL50	Daphnia	755.5 mg/L (48H) [1]
		[1] Método:Ecosar		
	Aquatic plants	CE50	Algae	154.9 mg/L (96H) [1]
		[1] Método:Ecosar		

12.2 Persistence and degradability.
No information is available regarding the biodegradability of the substances present.
No information is available on the degradability of the substances present.
No information is available about persistence and degradability of the product.
The product evaporates quickly and enters the gas phase at room temperature. Information on its persistence and degradability is not relevant.

12.3 Bioaccumulative potential.
Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
propan-2-ol, isopropyl alcohol, isopropanol CAS No: 67-63-0 EC No: 200-661-7	0,05	3	-	Very low
dimethyl ether CAS No: 115-10-6 EC No: 204-065-8	-0,07	-	-	Very low

12.4 Mobility in soil.
No information is available about the mobility in soil.
Soil or water contamination is unlikely due to high volatility of the product.

12.5 Results of PBT and vPvB assessment.
No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.
This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.
The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.
No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.
Dispose of packaging through the supplier. Transport, unloading, treatment or disposal activities may be subject to additional local/national legislation. Waste and empty containers must be handled and eliminated according to current, local/national legislation.
Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.
Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.
Transport documentation: Bill of lading

Air: Transport by plane: ICAO/IATA.
Transport document: Airway bill.

14.1 UN number or ID number.
UN No: UN1950

14.2 UN proper shipping name.
Description:
ADR/RID: UN 1950, AEROSOLS, 2.1, (D)
IMDG: UN 1950, AEROSOLS, 2.1 (-41ºC)
ICAO/IATA: UN 1950, AEROSOLS, 2.1

14.3 Transport hazard class(es).
Class(es): 2

14.4 Packing group.
Packing group: Not applicable.

14.5 Environmental hazards.
Marine pollutant: No
Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-D,S-U

14.6 Special precautions for user.
Labels: 2.1



Hazard number: Not applicable.
Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.
Proceed in accordance with point 6.
ADR LQ: 1 L
IMDG LQ: 1 L
ICAO LQ: Not applicable.

14.7 Maritime transport in bulk according to IMO instruments.
The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

Volatile organic compound (VOC)
VOC content (p/p): 100 %
VOC content: 744 g/l

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.
The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.
Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles:

Designation of the substance, of the group of substances or of the mixture	**Conditions of restriction**
3. Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F;	1. Shall not be used in: - ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, - tricks and jokes, - games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless

(b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	required for fiscal reasons, or perfume, or both, if they: - can be used as fuel in decorative oil lamps for supply to the general public, and, - present an aspiration hazard and are labelled with H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: (a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: 'Keep lamps filled with this liquid out of the reach of children'; and, by 1 December 2010, 'Just a sip of lamp oil - or even sucking the wick of lamps - may lead to life-threatening lung damage'; (b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter may lead to life threatening lung damage'; (c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010. .

Kind of pollutant to water (Germany): WGK 1: Slightly hazardous to water. (Autoclassified according to the AwSV Regulations)

15.2 Chemical safety assessment.
No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Classification codes:
Aerosol 1 : Flammable aerosol, Category 1
Eye Irrit. 2 : Eye irritation, Category 2
Flam. Gas 1A : Flammable gas, Category 1A
Flam. Liq. 2 : Flammable liquid, Category 2
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

Changes regarding to the previous version:
- Changes in the information of the supplier (SECTION 1.3).
- Change in the emergency number (SECTION 1.4).
- Modification in the values of the physical and chemical properties (SECTION 9).
- National legislative changes (SECTION 15.1).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method


It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Information on the TSCA Inventory (Toxic Substances Control Act) USA:

CAS No	Name	State

67-63-0	propan-2-ol, isopropyl alcohol, isopropanol	Registered
115-10-6	dimethyl ether	Registered

Risk classification system NFPA 704:



Health hazard: 2 (Hazardous)

Flammability: 4 (Below 73°F)

Reactivity: 1 (Unstable if heated)

Abbreviations and acronyms used:
ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.
AwSV: Facility Regulations for handling substances that are hazardous for the water.
BCF: Bioconcentration factor.
CEN: European Committee for Standardization.
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
EC50: Half maximal effective concentration.
PPE: Personal protection equipment.
IATA: International Air Transport Association.
ICAO: International Civil Aviation Organization.
IMDG: International Maritime Code for Dangerous Goods.
LC50: Lethal concentration, 50%.
LD50: Lethal dose, 50%.
NOEC: No observed effect concentration.
PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.
WGK: Water hazard classes.

Key literature references and sources for data:
http://eur-lex.europa.eu/homepage.html
http://echa.europa.eu/
Regulation (EU) 2020/878.
Regulation (EC) No 1907/2006.
Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.